



Architectural Hinges

Accessories



Set Screw Set

This set converts removable pin hinges to non-removable pin (set screw in barrel) hinges as required

100

- 1/8" x 10-32 Set Screws (qty. 300)
- 3/16" x 10-32 Set Screws (qty. 300)
- 3/32" Hex Key
- Hand Tap "T" Wrench
- 10-32 Tap
- #21 Drill Bit



Sleeve Bolt

For use in securing push bars, exposed door closers and other fixtures to doors 1 3/4" (45 mm) thick or greater

263 Aluminum

- 9/16" (14 mm) head sex nut with 1/4"-20 internal thread
- Knurled shoulder prevents bolt from turning
- Drill a 3/8" (9.5 mm) hole and insert the sex bolt
- Available in US2C finish only (compatible with US26D, US28 or US32D)



Molly Jack Nut (8S JN)

For use in properly anchoring various products to hollow metal frames 3/16" to 3/8" (4.8 to 9.5 mm) thick

265 Aluminum

- For use with the Hager Reinforcing Pivot Hinges (250 series)
- Easily installed by drilling a 7/16" (11.1 mm) pilot hole and following the instructions provided with each product



Hinge Reinforcement Plate

305 Steel

- For metal frames
- Four holes

Hinge Size		Width		Total Length		Offset	Gauge of metal	Tapped for screw
Inches	mm	Inches	mm	Inches	mm			
4 1/2	114	1 1/2	38	10	254	0.074	0.154	12-24



Back Plate

417 Steel

- For wood doors
- For full or half surface hinges

Length		Width		Gauge of metal	Number of holes	Machine Screw Size
Inches	mm	Inches	mm			
4 1/2	114	1 13/16	46	0.074	3	1/2 x 12-24
5	127	2 1/8	54	0.089	4	1/2 x 12-24

Decorator Tip Kits

Conversion tips and pins for architectural grade hinges



1712 Ball Standard Weight

1713 Ball Heavy Weight



1716 Acorn Standard Weight

1717 Acorn Heavy Weight



1722 Steeple Standard Weight

1723 Steeple Heavy Weight



1728 Urn Standard Weight

1729 Urn Heavy Weight

- Standard Weight Hinge Size - 3 1/2", 4", 4 1/2", 5"
- Heavy Weight Hinge Size - 4 1/2", 5"
- Solid brass with stainless steel pin